

## 24' HIGHBOY EQUIPMENT TRAILER

MODEL# ET24TR-25 GVWR: 63.000lbs TARE: 9200 lbs

## **GENERAL SPECIFICATIONS**

Dimensions: Deck Length 24', Outside Width 9', Overall Length 33' (Owner must carry annual over-width

permit)

Landing Gear: 55,000lb SAF Holland Atlas 55 2 Speed Landing Gear

Pintle Eye: Adjustable Pintle Eye, Forged, 100,000lb, Heavy duty Safety Chains & Hooks

Frame: High Strength Engineered Beam w/1.5" Camber

**Deck:** 35" Deck Height, Floor- SPF Rough Plank Decking, 8" Channel outside Frame, 3" Superlite I Beam Crossmembers, 1/4" Checkerplate over Wheels, 12 Heavy Duty Recessed D-rings (6 Per side), Raised Front

Bolster

Beavertail: Full Width with 2 - 19" Sliding Spring Assisted Heavy Duty Ramps

Air System: Standard Air Tanks

**Tires:** 255/70R22.5 Cooper Road Master On/Off Road **Rims:** 22.5" x 8.25" Steel Powder-coated (inner & outer)

Data: Meets or Exceeds all Canadian Motor Vehicle Safety Standards

Suspension: Hutch Spring Ride with Three 25,000lb Axles @ 96" Spread, 17" Ride Height, 77 1/2" Track

Width, Stemco Wheel Seals, EP2 Lithium Greased Hub System

**Brakes:** 16.5" x 7" Extended Life Antilock Braking System, Bendix TABS-6 ABS (2 Sensors/1 Modulator), Meritor Auto Slack Adjusters, Spring Brake Pots 30/30 TSE, 23.75" Cam Length – Dexter Wheel End Cast Hub and Drum

## STANDARD FEATURES

Coating: Complete Steel Shot Blasted. Epoxy Primer Inside and Out. Top Coat PPG Urethane, All Painted

Parts Baked in Heat Ovens

**Colors:** Black or Charcoal (custom colors available – see options)

Bumpers: Rear Light Bar Document Holder: Included Safety: Reflective Tape

Lighting: HD Sealed Wiring Harness System, Rubber Mounted LED as per CMVSS with Side Signals

Mudflaps: RENN Mudflaps at Front & Rear of Axles

**Tool Box:** A-Frame Tool Box **Step:** Driver Side Mounted Step



