



SLDD-53 TRIDEM AXLE 53' DROP DECK TRAILER



Standard Features

Safety:	Reflective Tape
Coating:	All Components Steel Shot Blasted, PPG Zinc Rich Epoxy Primer Inside and Out, Top Coat PPG Urethane, All Painted Parts Baked in Heat Ovens
Bumper:	Meets CMVSS
Colors:	Black
Lighting:	HD Sealed Wiring Grote Harness System, 6 Grote 4" round LED stop/tail/turn LED w/anti-theft bezels as per CMVSS 9- 3/4" Grote Micro Nova per side, 1 signal/marker per side 5-3/4" micro nova in rear bolster, 4-pullout style wide load lights, Aux 2 pin plug at rear
Dock Bumper:	Two Mounted Rear
Tow Hooks:	One Installed Rear
Document Holder:	Included
Mudflaps:	4 in Front of Landing Gear, 1 behind rear wheels
Control Box:	Air load scale and Dump Valve in Aluminum Box – Mounted on DS in Front of Landing Gear

Specifications

Dimension Notes:	Deck Length 53, Outside Width 102", Overall Length 53', Top Deck 11', Bottom Deck 42'
Deck:	40" Rear Loaded Deck Height, 49" King Pin Plate Height, Floor- 1-1/8 Floor-1-5/16 BC Douglas FIR shiplap, 6" – 3/16" Formed Outside Rails, 12" Centers 4" Superlite I Beam Crossmembers, 2-1/2" Full 3/8" Rub Rail, Stake Pockets @ 24" Centers, 26 Winches 13 per Side w/Opposite J-Hooks, Pipe Spools between Stake Pockets, Front Stake Pockets, HD Tarp hooks, 2.5" camber
Suspension:	Hendrickson AAL23K INTRAAX Air Ride with 3-23,000lb axles, 60"-60" Spread - Kingpin to C/L Center Axle: 40.875", 8" Ride Height, 77 1/2" Track Width, HXL5 Wheel Seals Federal Mogul
Data:	Meets or Exceeds all Canadian Motor Vehicle Safety Standards
Air System:	Standard Air Tanks, Air Filter System, Manual Dump
Tool Box:	1 Aluminum Box with Barn Doors 18"h x 23"d x 60"
Landing Gear:	Pair - 62500 lb. Dual Speed SAF Holland Mark V
Brakes:	16.5" x 7" Extended Life Antilock Braking System 20,000lb Rating, Bendix TABS-6 ABS (2 Sensors/1 Modulator), Haldex Auto Slack Adjusters, Spring Brake Pots 30/30 TSE, Short 28 Spline Cam Wheel End Cast Hub and Drum
Rims:	22.5" x 8.25" Aluminum or Steel Powder-coated (inner & outer)
Frame:	One Piece Seamless Web & Flange 130,000psi – Robotically Welded
Tires:	255/70R22.5 Cooper RM872
Distributed Load:	68,000 lb., 10' Concentrated-55,000 lb., 4' Concentrated-55,000 lb., Tare Weight- Approx 14,000lbs
Kingpin:	18" Pin setting



Specs are subject to change without notice. Please contact Southland Trailer Corp Product Specialist for price con irmation on all Products. - Revised August 2023